OSCILLATING SPRINKLERS

The Compact line is the ideal choice for watering your lawn, as it has an adjustable jet that simulates light rain.

The elegant design of the outer casing in ABS, a sturdy turbine engine and resistant gears make this line one of Claber's most successful. Thanks to the special Aqua Control system, it could not be any easier to adjust the coverage of the area you want to water with just 2 fingers!



COMPACT-160 PROMO







Oscillating sprinkler, 14 precision punched water holes providing uniform distribution with natural rain effect. Control knob for selection of 4 main spray patterns with many intermediate steps. Irrigated area max 180 m².

Bar	m²	m	I/min
1	78	11,0 x 7,0	8,0
2	133	14,0 x 10,0	11,0
3	165	16,0 x 11,0	13,0
4	181	16.0 x 11.0	15.0

code	packaging qty	pack size (cm)	box size (cm)	volume (m³)	weight (kg)	pcs/pallet	
8740	4	41 x 10 x 15,5	46,2 x 26,2 x 17	0,021	1,66	140	8 000625 087402

COMPACT-12

8748





Oscillating arm in ABS, available with 12 holes, this model is supplied complete with hydraulic motor and self-lubrificating nonwearing acetal resin gears.
The new large-diameter turbine offers high performance even at low pressure, while the new watering selection device, comprising a pratical click-operated selector provides 5 different water settings. A sled in aluminium sections (Ø 10 mm) ensures excellent stability and easy trailing.

Irrigated area máx 190 m².

Bar

100

215

320

Bar

1

2 3

m²

98

169

192

I/min

9.1

14.1

I/min

10,5

19,0

21,0

15,5

12,4

15,7

m

11.5 x 8.5

14,5 x 11,5

17.5 x 11.0

16,5 x 10,0

m

10,5 x 9,5

16.0 x 13.4 18,8 x 16,2

19,2 x 16,7

code	packaging	qty	pack size (cm)	box size (cm)	volume (m³)	weight (kg)		
8748		3	32 x 8,5 x 19	20 x 30 x 33	0,019	1,86	144	8 000625 087488

COMPACT-20 **AQUA CONTROL**

8753





The oscillating arm in ABS complete with the exclusive "Aqua Control" system allows to vary coverage of the irrigated area as required. Available with 20 holes and 8 adjustable nozzles (complete with knurled end for secure connection), this model is supplied complete with hydraulic motor and self-lubrificating non-wearing acetal résin gears. The new large-diameter turbine offers high performance even at low pressure, while the new watering selection device, comprising a pratical click-operated selector provides 5 different water settings. A sled in aluminium sections (Ø 10 mm) ensures excellent stability

and easy training, impated area max 320 m.							
code	packaging qty	pack size (cm)	box size (cm)	volume (m³)	weight (kg)	pcs/pallet	
8753	3	32 x 8 5 x 19	20 v 30 v 33	0.019	1 87	144	8 000625 087532

COMPACT-16 SUPER METAL





The oscil guarante

The large motor w large-sec comprise the sled base, guarantee excellent stability and easy trailing.

wwlrrigated area max 290 m².

illating aluminium arm with 16 brass nozzles	Bar	\mathbf{m}^2	m	I/min
ees regular water jet operation.	1	83	10,1 x 8,2	11,8
e sized sturdy ABS body houses the hydraulic	2	202	16,4 x 12,3	18,0
which may be opened for inspection while the	3	269	19,2 x 14,0	21,5
ction aluminium elements (Ø 15 mm), which	4	290	19,9 x 14,6	25,0
o the cled bace guarantee evcellent stability and				

code	packaging qty	pack size (cm)	box size (cm)	volume (m³)	weight (kg)	pcs/pallet	
87/13	3	/13 v Q v 22 5	25 v 30 v 45	0.034	2.48	72	8 000625 087433