

COLIBRI® SYSTEM

With the Colibri System, Claber brings all of the advantages of underground irrigation into small green spaces too! It is easy to use, saves on water, keeps your lawn and plants looking good and healthy, and makes the most of your garden. Colibri is easy to install, with no need to dig large holes or connect up to the power mains. All you need is one of Claber's battery-powered timers connected to the tap to make sure your garden has just the right amount of water at the right time, even when you are away or on holiday. And with the new jet adjustment, you just need two fingers for perfect, targeted irrigation with no waste!



COLIBRI® SYSTEM

Underground irrigation
for small gardens



EXTERNAL JET ADJUSTMENT
WITH JUST TWO FINGERS

WASHABLE FILTER

STAINLESS STEEL RETURN SPRING

NON-SPILL RUBBER VALVE
WITH FROST-RESISTANT
DEVICE

GEAR-DRIVEN TURBINE
WITH JET-INTERCEPTING HEAD

BODY AND ROD
IN SHOCKPROOF ABS

INFO



360° COLIBRÌ MICRO-SPRINKLER 90210



180° COLIBRÌ MICRO-SPRINKLER 90220



90° COLIBRÌ MICRO-SPRINKLER 90230



Underground micro-sprinkler with low water consumption. Ideal for watering vegetable patches and small gardens, even at low pressure.
Gear-driven device made from acetal resin.
External adjustment of range.
Micro-sprinkler is connected to the 1/2" (13-16 mm) main hose by means of the 1/2" (15-21 mm) threaded 3-way connector (cod. 91072/91017) or 1/2" (15-21 mm) threaded elbow (cod. 91082/91019/91021).

Height from ground: 2" (5 cm).



code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet
90210		12	4 x 14,3 x 4	23,7 x 17,5 x 16,5	0,007	1,10	1512
90220		12	4 x 14,3 x 4	23,7 x 17,5 x 16,5	0,007	1,10	1512
90230		12	4 x 14,3 x 4	23,7 x 17,5 x 16,5	0,007	1,10	1512

90210

360°				r	
BAR	l/min	m ²			
1,5	4,0	38,5	r 3,5 m	5,0 m	
2,0	4,5	50,2	r 4,0 m	5,7 m	
3,0	5,1	63,6	r 4,5 m	6,4 m	

90220

180°				r	
BAR	l/min	m ²			
1,5	2,9	25,1	r 4,0 m	5,7 m	
2,0	3,3	31,8	r 4,5 m	6,4 m	
3,0	3,6	34,7	r 4,7 m	6,7 m	

90230

90°				r	
BAR	l/min	m ²			
1,5	1,7	9,6	r 3,5 m	5,0 m	
2,0	2,0	13,8	r 4,2 m	6,0 m	
3,0	2,1	13,8	r 4,2 m	6,0 m	


GUARD COLLAR

90250



For optimum installation of Colibrì micro-sprinklers.
Traps sand and pebbles from the soil.
Bag of 1 pc.

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet
90250		10	12 x 15,5 x 3,5	10 x 39 x 13	0,005	0,38	1280



COLIBRÌ STARTER KIT

90200




Starter kit for an underground watering system for 50 m² garden, complete with Colibrì System micro-sprinklers. Additional micro-sprinklers and Colibrì System accessories are also available as required.
The compact colour packaging features easy assembly instructions of all kit components.

CONTAINS

3291	Main tube 25 m	x 1	91072	1/2" (15-21 mm) threaded 3 - way connector	x 3
91347	1/2" hose threaded adaptor	x 1	90920	Threaded drainage valve	x 1
91494	3/4" automatic adaptor	x 1	90210	360° - 2" micro-sprinkler	x 1
91081	1/2" elbow coupling	x 5	90220	180° - 2" micro-sprinkler	x 4
91071	1/2" tee	x 2	91096	Tube clamp	x 24
91082	1/2" (15-21 mm) threaded elbow	x 2	90250	Guard collars	x 5

code	packaging	qty	pack size (cm)	box size (cm)	volume (m³)	weight (kg)	pcs/pallet
90200		1	40 x 40 x 12	40 x 40 x 12	0,019	2,70	54

EXAMPLE OF SYSTEM WITH THE COLIBRÌ STARTER KIT



MAIN REQUIREMENTS:

- Pressure: minimum 2.5 bars
- Flow rate: at least 21 l/min
- Garden shape: regular (square or slightly rectangular; e.g. 7 x 7 m, 8 x 7 m, 8 x 8 m)
- Water supply: water mains

FEATURES:

- The kit comes with fixed angle sprinklers (1 x 360°, 4 x 180°)
- Colibrì sprinklers have a jet of min. 3.5 m - max. 4.5 m
- The area behind the sprinklers is also watered for about 30-40 cm.



The underground micro-irrigation system created with the Colibrì Starter Kit can easily be automated by using a Claber one-way tap timer (Aquauno, Aquauno Plus and Tempo, from page 88).






TURBO-JET 80°-360° - 3"

90264



80°-360°

Dynamic pop-up sprinkler featuring low water consumption.
Ideal for small gardens, even with low water pressure.
Special internal gear mechanism rotating at constant speed, guaranteeing balanced watering.
Working arc adjustable from 80° to 360°. Jet range adjustable by turning the ring nut.
Inspectable and washable filter. Standard 1/2" (15-21 mm) threaded base.
Height from ground 3" (cm 7,5).
Packs of 12 pcs.

							
BAR	l/min	r	l/min	r	l/min	r	
1,5	1,48	4,0	4,8 m	2,56	3,5	4,2 m	4,67
2,0	1,73	4,5	5,4 m	2,85	4,5	5,4 m	5,27
3,0	2,07	5,25	6,3 m	3,46	5,0	6,0 m	6,41

code	packaging	qty	pack size (cm)	box size (cm)	volume (m³)	weight (kg)	pcs/pallet
90264		12	5,1 x 14 x 5,1	10 x 39 x 13	0,005	1,10	1536






TURBO-JET 80°-360° - 4"

90266



80°-360°

Dynamic pop-up sprinkler featuring low water consumption.
Ideal for small gardens, even with low water pressure.
Special internal gear mechanism rotating at constant speed, guaranteeing balanced watering.
Working arc adjustable from 80° to 360°. Jet range adjustable by turning the ring nut.
Inspectable and washable filter. Standard 1/2" (15-21 mm) threaded base.
Height from ground 4" (cm 10).
Packs of 12 pcs.

									
BAR	l/min	r		l/min	r		l/min	r	
1,5	1,48	4,0	4,8 m	2,56	3,5	4,2 m	4,67	3,6	4,3 m
2,0	1,73	4,5	5,4 m	2,85	4,5	5,4 m	5,27	4,25	5,1 m
3,0	2,07	5,25	6,3 m	3,46	5,0	6,0 m	6,41	5,0	6,0 m

code	packaging	qty	pack size (cm)	box size (cm)	volume (m³)	weight (kg)	pcs/pallet
90266		12	5,1 x 14 x 5,1	10 x 39 x 13	0,005	1,16	1536

