

SOLENOID VALVES

This range of solenoid valves is reliable and long-lasting, thanks to the materials they are made of: metal parts are made of stainless steel and the body of nylon reinforced with glass fibre. 100% tried and tested, even at high pressure, they feature a manual opening/shut-off and solenoid rotation control. With a slow shut-off device to prevent pressure shock, solenoid valves have an operating pressure of 0.5-12 bar. Thanks to the new solenoid fitted with an anti-sand filter, which collects the impurities in the water and filters them from the irrigation circuit, Claber solenoid valves are top of the range.

9 V - 1" (26-34 mm) FEMALE SOLENOID VALVE

90812



Solenoid valve equipped with solenoid with anti-sand filter. Works with the Multipla 9V timer (cod. 8060) or with the 9V control unit (cod. 90821). With 1" (26-34 mm) female inlet and outlet thread. Body in fibre glass reinforced nylon, stainless steel metal components. Low speed shut-off device to prevent pressure shock. Optional manual opening/shut-off control. Operating pressure from 0,5 to 12 bar. Flow rate from 4,6 to 96 l/min. Operating temperature range +5° to +70°.

| code | packaging | qty | pack size (cm) | box size (cm) | volume (m ³) | weight (kg) | pcs/pallet | barcode |
|-------|-----------|-----|-------------------|-------------------|--------------------------|-------------|------------|------------------|
| 90812 | | 1 | 12,7 x 15,3 x 7,5 | 12,7 x 15,3 x 7,5 | 0,001 | 0,40 | 336 | 8 000625 90812 1 |

9 V - 1" (26-34 mm) MALE SOLENOID VALVE

90813



Solenoid valve equipped with solenoid with anti-sand filter. Works with the Multipla 9V timer (cod. 8060) or with the 9V control unit (cod. 90821). With 1" (26-34 mm) male inlet and outlet thread. Body in fibre glass reinforced nylon, stainless steel metal components. Low speed shut-off device to prevent pressure shock. Optional manual opening/shut-off control. Operating pressure from 0,5 to 12 bar. Flow rate from 4,6 to 96 l/min. Operating temperature range +5° to +70°.

| code | packaging | qty | pack size (cm) | box size (cm) | volume (m ³) | weight (kg) | pcs/pallet | barcode |
|-------|-----------|-----|-------------------|-------------------|--------------------------|-------------|------------|------------------|
| 90813 | | 1 | 12,7 x 15,3 x 7,5 | 12,7 x 15,3 x 7,5 | 0,001 | 0,40 | 336 | 8 000625 90813 4 |

24 V - 1" (26-34 mm) FEMALE SOLENOID VALVE

90814



Solenoid valve equipped with solenoid with anti-sand filter. Reinforced structure to withstand mechanical and thermal stresses. Operates with all types of multi-line timers at 24 V AC. With 1" (26-34 mm) female inlet and outlet thread. Body in fibre glass reinforced nylon, stainless steel metal components. Low speed shut-off device to prevent pressure shock. Optional manual opening/shut-off control. Operating pressure from 0,5 to 12 bar. Flow rate from 4,6 to 96 l/min. Operating temperature range +5° to +70°.

| code | packaging | qty | pack size (cm) | box size (cm) | volume (m ³) | weight (kg) | pcs/pallet | barcode |
|-------|-----------|-----|-------------------|-------------------|--------------------------|-------------|------------|------------------|
| 90814 | | 1 | 12,7 x 15,3 x 7,5 | 12,7 x 15,3 x 7,5 | 0,001 | 0,40 | 336 | 8 000625 90814 1 |

24 V - 1" (26-34 mm) MALE SOLENOID VALVE

90815



Solenoid valve equipped with solenoid with anti-sand filter. Reinforced structure to withstand mechanical and thermal stresses. Operates with all types of multi-line timers at 24 V AC. With 1" (26-34 mm) male inlet and outlet thread. Body in fibre glass reinforced nylon, stainless steel metal components. Low speed shut-off device to prevent pressure shock. Optional manual opening/shut-off control. Operating pressure from 0,5 to 12 bar. Flow rate from 4,6 to 96 l/min. Operating temperature range +5° to +70°.

| code | packaging | qty | pack size (cm) | box size (cm) | volume (m ³) | weight (kg) | pcs/pallet | barcode |
|-------|-----------|-----|-------------------|-------------------|--------------------------|-------------|------------|------------------|
| 90815 | | 1 | 12,7 x 15,3 x 7,5 | 12,7 x 15,3 x 7,5 | 0,001 | 0,40 | 336 | 8 000625 90815 8 |