OSCILLATING SPRINKLERS

The Compact line is the ideal choice for watering your lawn, as it has an adjustable jet that simulates light rain.

The elegant design of the outer casing in ABS, a sturdy turbine engine and resistant gears make this line one of Claber's most successful. Thanks to the special Aqua Control system, it could not be any easier to adjust the coverage of the area you want to water with just 2 fingers!



COMPACT-160 PROMO

8740





Oscillating sprinkler, 14 precision punched water holes providing uniform distribution with natural rain effect. Control knob for selection of 4 main spray patterns with many intermediate steps. Irrigated area max 180 m².

Bar	m²	m	I/min
1	78	11,0 x 7,0	8,0
2	133	14,0 x 10,0	11,0
3	165	16,0 x 11,0	13,0
4	181	16,0 x 11,0	15,0

code	packaging qty	pack size (cm)	box size (cm)	volume (m³)	weight (kg)	pcs/pallet	
8740	4	41 x 10 x 15,5	46,2 x 26,2 x 17	0,021	1,66	140	8 000625 087402

COMPACT-12

8748





Oscillating arm in ABS, available with 12 holes, this model is supplied complete with hydraulic motor and self-lubrificating nonwearing acetal resin gears.
The new large-diameter turbine offers high performance even at low pressure, while the new watering selection device, comprising a pratical click-operated selector provides 5 different water settings.
A sled in aluminium sections (Ø 10 mm) ensures excellent stability and easy trailing. Irrigated area max 190 m².

Bar	m²	m	I/min
1	98	11,5 x 8,5	9,1
2	169	14,5 x 11,5	12,4
3	192	17,5 x 11,0	14,1
4	165	16,5 x 10,0	15,7

I/min

10,5

19,0

15,5

21,0

m

10,5 x 9,5

16,0 x 13,4

18,8 x 16,2

19,2 x 16,7

code	packaging o	qty	pack size (cm)	box size (cm)	volume (m³)	weight (kg)	pcs/pallet	
8748		3	32 x 8,5 x 19	20 x 30 x 33	0,019	1,86	144	8 000625 087488

COMPACT-20 AQUA CONTROL

8753





The oscillating arm in ABS complete with the exclusive "Aqua Control" system allows to vary coverage of the irrigated area as required. Available with 20 holes and 8 adjustable nozzles (complete with knurled end for secure connection), this model is supplied complete with hydraulic motor and self-lubrificating non-wearing acetal résin gears. The new large-dian performance even at low pressi selection device, comprising a p selector provides 5 different wa aluminium sections (Ø 10 mm) en: and easy trailing. Irrigated area max 320 m².

incating non wearing acctai	
meter turbine offers high	
sure, while the new watering	
pratical click-operated	
ater settings. A sled in	
) ensures excellent stability	

Bar

2

m²

100

215

305

320

code	packaging q	Įty	pack size (cm)	box size (cm)	volume (m³)	weight (kg)	pcs/pallet	
8753		}	32 x 8,5 x 19	20 x 30 x 33	0,019	1,87	144	8 000625 087532

COMPACT-16 SUPER METAL

8743



The guar

The mot large comi easy trailing

cas, ca.				
Irrigated	area	max	290	m^2

oscillating aluminium arm with 16 brass nozzles	Bar	m²	m	I/min	
rantees regular water jet operation.	1	83	10,1 x 8,2	11,8	
large sized sturdy ABS body houses the hydraulic	2	202	16,4 x 12,3	18,0	
tor which may be opened for inspection while the	3	269	19,2 x 14,0	21,5	
e-section aluminium elements (Ø 15 mm), which nprise the sled base, quarantee excellent stability and	4	290	19,9 x 14,6	25,0	
iprise the sied base, guarantee excellent stability and					

code	packaging qty	pack size (cm)	box size (cm)	volume (m³)	weight (kg)	pcs/pallet	
8743	3	43 v 9 v 22 5	25 v 30 v 45	0.034	2 48	72	8 000625 087433