

# SOLENOID VALVES

This range of solenoid valves is reliable and long-lasting, thanks to the materials they are made of: metal parts are made of stainless steel and the body of nylon reinforced with glass fibre. 100% tried and tested, even at high pressure, they feature a manual opening/shut-off and solenoid rotation control. With a slow shut-off device to prevent pressure shock, solenoid valves have an operating pressure of 0.5-12 bar. Thanks to the new solenoid fitted with an anti-sand filter, which collects the impurities in the water and filters them from the irrigation circuit, Claber solenoid valves are top of the range.

## 9 V - 1" (26-34 mm) FEMALE SOLENOID VALVE

**90812**



Solenoid valve equipped with solenoid with anti-sand filter. Works with the Multipla 9V timer (cod. 8060) or with the 9V control unit (cod. 90821). With 1" (26-34 mm) female inlet and outlet thread. Body in fibre glass reinforced nylon, stainless steel metal components. Low speed shut-off device to prevent pressure shock. Optional manual opening/shut-off control. Operating pressure from 0,5 to 12 bar. Flow rate from 4,6 to 96 l/min. Operating temperature range +5° to +70°.

code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet
90812		1	16 x 13 x 8,2	16 x 13 x 8,2	0,002	0,38	288



## 9 V - 1" (26-34 mm) MALE SOLENOID VALVE

**90813**



Solenoid valve equipped with solenoid with anti-sand filter. Works with the Multipla 9V timer (cod. 8060) or with the 9V control unit (cod. 90821). With 1" (26-34 mm) male inlet and outlet thread. Body in fibre glass reinforced nylon, stainless steel metal components. Low speed shut-off device to prevent pressure shock. Optional manual opening/shut-off control. Operating pressure from 0,5 to 12 bar. Flow rate from 4,6 to 96 l/min. Operating temperature range +5° to +70°.

code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet
90813		1	16 x 13 x 8,2	16 x 13 x 8,2	0,002	0,37	288



## 24 V - 1" (26-34 mm) FEMALE SOLENOID VALVE

**90814**



Solenoid valve equipped with solenoid with anti-sand filter. Reinforced structure to withstand mechanical and thermal stresses. Operates with all types of multi-line timers at 24 V AC. With 1" (26-34 mm) female inlet and outlet thread. Body in fibre glass reinforced nylon, stainless steel metal components. Low speed shut-off device to prevent pressure shock. Optional manual opening/shut-off control. Operating pressure from 0,5 to 12 bar. Flow rate from 4,6 to 96 l/min. Operating temperature range +5° to +70°.

code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet
90814		1	16 x 13 x 8,2	16 x 13 x 8,2	0,002	0,38	288



## 24 V - 1" (26-34 mm) MALE SOLENOID VALVE

**90815**



Solenoid valve equipped with solenoid with anti-sand filter. Reinforced structure to withstand mechanical and thermal stresses. Operates with all types of multi-line timers at 24 V AC. With 1" (26-34 mm) male inlet and outlet thread. Body in fibre glass reinforced nylon, stainless steel metal components. Low speed shut-off device to prevent pressure shock. Optional manual opening/shut-off control. Operating pressure from 0,5 to 12 bar. Flow rate from 4,6 to 96 l/min. Operating temperature range +5° to +70°.

code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet
90815		1	16 x 13 x 8,2	16 x 13 x 8,2	0,002	0,37	288

