

# POP-UP SPRINKLERS

From Claber years of professional experience comes the pop-up sprinkler range. Designed and created to solve all your watering needs, these sprinklers are simple to use, while offering exclusive functional features. Claber pop-up come with 90°, 180° or 360° jets, or adjustable 0-350° jets. For long, narrow spaces there are square or rectangular area pop-up sprinklers. The jet can be easily adjusted at any time, using any standard hex key.



STAINLESS STEEL JET RANGE  
ADJUSTMENT SCREW  
WITH HEXAGONAL INSERT

WASHABLE FILTER TO ENSURE  
HIGH FILTERING POWER

STAINLESS STEEL RETURN  
SPRING

SELF-LUBRICATING CLUTCH  
(DELRIN) FOR  
ORIENTATION OF THE JET



SPECIAL PROFILE NOZZLE  
FOR UNIFORM, BALANCED  
JET DISTRIBUTION

HEAD ADJUSTABLE FROM 0°  
TO 350° WITH RING NUT  
SELF-LOCKING MECHANISM

BODY AND ROD MADE  
OF SHOCK-RESISTANT  
PLASTIC (ABS)

NON-SPILL RUBBER CHECK  
VALVE WITH  
FROST-RESISTANT DEVICE

SEALING GASKETS FOR  
LEAKAGE-FREE INSTALLATION

0° - 350° - 2" ADJUSTABLE  
POP-UP (5 cm)**90004**0° - 350° - 3" ADJUSTABLE  
POP-UP (7,5 cm)**90005**0° - 350° - 4" ADJUSTABLE  
POP-UP (10 cm)**90006**

Professional static sprinkler with 0-350° adjustable head. The choice of materials and quality of the production process are the guarantee of total reliability in any type of installation. The nozzle has a specially designed profile to ensure uniform and balanced water distribution. Stainless steel jet range adjustment screw. The standard 1/2" (15-21 mm) female connector allows it to be mounted on existing systems. Comes in pack of 24 pcs. Irrigated area max. 78 m<sup>2</sup>.

code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90004		24	3,7 x 10,9 x 3,7	20 x 39 x 13	0,010	1,45	1728	
90005		24	3,7 x 13,4 x 3,7	20 x 39 x 13	0,010	1,60	1728	
90006		24	3,7 x 16 x 3,7	20 x 39 x 13	0,010	1,80	1728	



0°-350°	90°	180°	270°	350°	r	
BAR	l/min	l/min	l/min	l/min		
1,5	2,8	5,3	7,7	9,2	r 4,0 m	5,7 m
2,0	3,3	5,8	9,0	10,8	r 4,5 m	6,4 m
3,0	4,0	6,9	10,8	13,0	r 5,0 m	7,1 m

ADJUSTABLE POP-UP 0° - 350°  
6 L/MIN - 2" (5 cm)**90020**ADJUSTABLE POP-UP 0° - 350°  
6 L/MIN - 4" (10 cm)**90019**

A professional-quality static pop-up sprinkler with an adjustable head from 0° to 350°, that guarantees even irrigation and minimal water consumption (6 l/min). It is equipped with a screw to adjust the jet with a hexagonal insert, stainless steel return spring, filter, self-lubricating clutch and non-spill rubber valve with an anti-freeze device. The standard 1/2" (15-21 mm) female connector allows it to be mounted on existing systems. Comes in pack of 24 pcs. Irrigated area max. 55 m<sup>2</sup>.

code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90020		24	3,7 x 10,9 x 3,7	20 x 39 x 13	0,010	1,42	1728	
90019		24	3,7 x 16 x 3,7	20 x 39 x 13	0,010	1,80	1728	



0°-350°	90°	180°	270°	350°	r	
BAR	l/min	l/min	l/min	l/min		
1,5	2,0	3,3	4,5	6,0	r 3,7 m	5,3 m
2,0	2,2	3,6	5,2	6,8	r 4,0 m	5,7 m
3,0	2,5	4,4	6,4	8,2	r 4,2 m	6,0 m

0° - 350°  
ADJUSTABLE HEAD**90007**

Made of shock-resistant ABS plastic.  
Filter with support provided.  
Stainless steel jet range adjustment screw.  
Compatible with other brand sprinklers.  
Blister of 1 pc.



code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90007		12	7,9 x 15,7 x 2,8	25 x 19 x 10	0,005	0,30	1728	

360° JET POP-UP - 2" (5 cm)

90041



Professional static sprinkler with 360° head. The choice of materials and quality of the production process are the guarantee of total reliability in any type of installation. The nozzle has a specially designed profile to ensure uniform and balanced water distribution. Stainless steel jet range adjustment screw.

360° JET POP-UP - 4" (10 cm)

The standard 1/2" (15-21 mm) female connector allows it to be mounted on existing systems. Comes in pack of 12 pcs. Irrigated area max. 58 m<sup>2</sup>.

90043



code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90041		12	3,7 x 11 x 3,7	10 x 39 x 13	0,005	0,78	1440	8 000625 900411
90043		12	3,7 x 16 x 3,7	10 x 39 x 13	0,005	0,93	1440	8 000625 900435



360°			r	
BAR	l/min	m <sup>2</sup>		
1,5	8,2	43,0	r 3,7 m	5,3 m
2,0	9,5	50,3	r 4,0 m	5,7 m
3,0	11,5	56,7	r 4,3 m	6,0 m

360° HEAD

90044



Made of shock-resistant ABS plastic. Filter with support provided. Stainless steel jet range adjustment screw. Compatible with other brand sprinklers. Blister of 1 pc.



code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90044		12	7,9 x 15,7 x 2,8	25 x 19 x 10	0,005	0,30	1728	8 000625 900442

180° JET POP-UP - 2" (5 cm)

90053



Professional static sprinkler with 180° head. The choice of materials and quality of the production process are the guarantee of total reliability in any type of installation.

180° JET POP-UP - 4" (10 cm)

The nozzle has a specially designed profile to ensure uniform and balanced water distribution. Stainless steel jet range adjustment screw. The standard 1/2" (15-21 mm) female connector allows it to be mounted on existing systems. Comes in pack of 12 pcs. Irrigated area max. 31,8 m<sup>2</sup>.

90055



code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90053		12	3,7 x 11 x 3,7	10 x 39 x 13	0,005	0,78	1440	8 000625 900534
90055		12	3,7 x 16 x 3,7	10 x 39 x 13	0,005	0,95	1440	8 000625 900558



180°			r	
BAR	l/min	m <sup>2</sup>		
1,5	5,1	25,1	r 4,0 m	5,7 m
2,0	6,0	29,0	r 4,3 m	6,0 m
3,0	7,1	31,8	r 4,5 m	6,4 m

180° HEAD

90056



Made of shock-resistant ABS plastic. Filter with support provided. Stainless steel jet range adjustment screw. Compatible with other brand sprinklers. Blister of 1 pc.



code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90056		12	7,9 x 15,7 x 2,8	25 x 19 x 10	0,005	0,30	1728	8 000625 900565

## 90° JET POP-UP - 2" (5 cm)

**90095**

Professional static sprinkler with 90° head. The choice of materials and quality of the production process are the guarantee of total reliability in any type of installation. The nozzle has a specially designed profile to ensure uniform and balanced water distribution.

Stainless steel jet range adjustment screw.

The standard 1/2" (15-21 mm) female connector allows it to be mounted on existing systems. Comes in pack of 12 pcs. Irrigated area max. 12,6 m<sup>2</sup>.

## 90° JET POP-UP - 4" (10 cm)

**90097**


code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet
90095		12	3,7 x 11 x 3,7	10 x 39 x 13	0,005	0,78	1440
90097		12	3,7 x 16 x 3,7	10 x 39 x 13	0,005	0,93	1440

8	
---	--

8	
---	--



90°			r	
BAR	l/min	m <sup>2</sup>		
1,5	2,8	8,6	r3,3 m	4,6 m
2,0	3,2	9,6	r3,5 m	4,9 m
3,0	3,9	12,6	r4,0 m	5,7 m



## 90° HEAD

**90098**

Made of shock-resistant ABS plastic.  
Filter with support provided.  
Stainless steel jet range adjustment screw.  
Compatible with other brand sprinklers.  
Blister of 1 pc.



code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet
90098		12	7,9 x 15,7 x 2,8	25 x 19 x 10	0,025	0,30	1728

8	
---	--



### SQUARE AREA POP-UP - 4" (10 cm)

**90133**


Professional static sprinkler with square area. The choice of materials and quality of the production process are the guarantee of total reliability in any type of installation. The nozzle has a specially designed profile to ensure uniform and balanced water distribution. Stainless steel jet range adjustment screw. The standard 1/2" (15-21 mm) female connector allows it to be mounted on existing systems. Height from ground 4" (10 cm). Comes in pack of 12 pcs. Irrigated area max. 64 m<sup>2</sup>.

BAR	l/min	m <sup>2</sup>	A B	
1,5	8,9	36,0	6 x 6 m	5,5 m
2,0	10,3	49,0	7 x 7 m	6,3 m
3,0	12,6	64,0	8 x 8 m	7,3 m

code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90133		12	3,7 x 16 x 3,7	10 x 39 x 13	0,005	0,95	1440	8 000625 901333

### SQUARE AREA HEAD

**90134**


Square area head: made of shock-resistant ABS plastic. Filter with support provided. Stainless steel jet range adjustment screw. Compatible with other brand sprinklers. Blister of 1 pc.



code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90134		12	7,9 x 15,7 x 2,8	25 x 19 x 10	0,005	0,30	1728	8 000625 901340

### CENTRE-STRIP POP-UP - 4" (10 cm)

**90109**


Professional static sprinkler with centre-strip. The choice of materials and quality of the production process are the guarantee of total reliability in any type of installation. The nozzle has a specially designed profile to ensure uniform and balanced water distribution. Stainless steel jet range adjustment screw. The standard 1/2" (15-21 mm) female connector allows it to be mounted on existing systems. Height from ground 4" (10 cm). Comes in pack of 12 pcs. Irrigated area max. 20,3 m<sup>2</sup>.

BAR	l/min	m <sup>2</sup>	A B	
1,5	6,8	13,2	12,0 x 1,1 m	
2,0	8,3	17,2	13,2 x 1,3 m	
3,0	10,2	20,3	13,5 x 1,5 m	1,2 m

code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90109		12	3,7 x 16 x 3,7	10 x 39 x 13	0,005	0,97	1440	8 000625 901098

### CENTRE-STRIP HEAD

**90110**


Centre-strip head: made of shock-resistant ABS plastic. Filter with support provided. Stainless steel jet range adjustment screw. Compatible with other brand sprinklers. Blister of 1 pc.



code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90110		12	7,9 x 15,7 x 2,8	25 x 19 x 10	0,005	0,30	1728	8 000625 901104

**END-STRIP POP-UP - 4"**  
(10 cm)**90121**

Professional static sprinkler with end-strip. The choice of materials and quality of the production process are the guarantee of total reliability in any type of installation. The nozzle has a specially designed profile to ensure uniform and balanced water distribution. Stainless steel jet range adjustment screw. The standard 1/2" (15-21 mm) female connector allows it to be mounted on existing systems. Height from ground 4" (10 cm). Comes in pack of 12 pcs. Irrigated area max. 11,2 m<sup>2</sup>.

BAR	l/min	m <sup>2</sup>	A B	
1,5	3,8	8,0	8,0 x 1,0 m	
2,0	4,4	9,1	8,3 x 1,1 m	
3,0	5,4	11,2	9,3 x 1,2 m	

code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90121		12	3,7 x 16 x 3,7	10 x 39 x 13	0,005	0,95	1440	8 000625 901210

**END-STRIP HEAD****90122**

End-strip head: made of shock-resistant ABS plastic. Filter with support provided. Stainless steel jet range adjustment screw. Compatible with other brand sprinklers. Blister of 1 pc.

code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90122		12	7,9 x 15,7 x 2,8	25 x 19 x 10	0,005	0,31	1728	8 000625 901227

**SET OF POP-UP SPARE PARTS****90124**

Set of spare parts comprising:  
- 2 pop-up ring nuts  
- 4 pop-up sealing gaskets for Pop-up, Colibri and Turbo-Jet.

code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90124		12	7,9 x 15,7 x 2,8	25 x 19 x 10	0,005	0,46	1728	8 000625 901241

**SET OF SPARE POP-UP AND COLIBRI FILTERS****90123**

5 replacement filters for Pop-up and Colibri sprinklers.

code	packaging	qty	pack size (cm)	box size (cm)	volume (m <sup>3</sup> )	weight (kg)	pcs/pallet	
90123		12	7,9 x 15,7 x 2	25 x 19 x 10	0,005	0,33	1728	8 000625 901234

