

STATIC AND ROTATING SPRINKLERS

Claber static and rotating sprinklers offer you all of this: a great look, ease of use, versatile features and a vast range of solutions to meet different needs. From compact models, easy to move across the lawn, to models on spike to be firmly anchored into the ground, without damaging your grass.

Watering is always even and just like natural rainfall, even at low water pressure.



MULTIFUNCTION SPRINKLER

8654


Made entirely in ABS. Special round shape allows easy dragging over lawns, between flower beds and plants. Shaped upper section for easily lifting. Flange rotates to provide 6 different patterns. Irrigated area max 64 m².

Bar	m ²	Ø m	l / min
1	36	6,0	17,5
2	64	8,0	24,7
3	64	8,0	30,3
4	64	8,0	34,0

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet	
8654		3	20 x 24 x 8	25 x 26 x 23	0,015	1,30	135	8 000625 086542

ROLLINA

8656


Compact, contoured design for easy movement over lawns. The new 5-blade rotor intercepts the water jets to create a fine natural rain effect. Irrigated area max 28 m².

Bar	m ²	Ø m	l / min
1	19	5,0	16,5
2	23	6,0	24,0
3	28	6,0	28,0
4	28	6,0	33,0

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet	
8656		5	11 x 24 x 6,5	28 x 13 x 25	0,009	0,84	360	8 000625 086560

TURBOSPRUZZO

8658


Compact, contoured design for easy movement over lawns. Stationary sprinkler produces a fine spray for watering circular areas. Irrigated area max 63 m².

Bar	m ²	Ø m	l / min
1	58	9,0	18,0
2	63	9,0	24,0
3	57	8,0	27,0
4	47	8,0	30,0

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet	
8658		6	11 x 24 x 5	28 x 13 x 25	0,009	0,95	432	8 000625 086580

TURBOSPIKE

8660


Stationary sprinkler on plastic spike with natural rain effect in circle pattern. Irrigated area max 40 m².

Bar	m ²	Ø m	l / min
1	30	6,0	7,8
2	30	6,0	10,7
3	40	7,0	12,9
4	40	7,0	14,8

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet	
8660		12	7,9 x 24 x 3,8	28 x 13 x 25	0,009	0,89	864	8 000625 086603



IDROSPRAY 2000

8675



Rotating 2-arm sprinkler constructed entirely in ABS. Special rounded design enables easy movement over lawn. Offset nozzle jets in fan arrangement achieve a uniform spray and magnificent water games. Adjustable nozzles optimise performance also at low pressure. Covers circular areas with light rain effect. Irrigated area max 177 m².

Bar	m ²	Ø m	l / min
1	123	12,5	14,0
2	177	15,0	17,8
3	143	13,5	20,5
4	123	12,5	23,0

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet	
8675		2	25,5 x 22 x 12	25 x 26 x 23	0,015	1,12	90	8 000625 086757

AQUALUX 2000

8685



LIMITED STOCK



Rotating 2-arm sprinkler constructed entirely in ABS. Special rounded design enables easy movement over lawn. Adjustable nozzles optimise performance also at low pressure. Covers circular areas with light rain effect. Irrigated area max 113 m².

Bar	m ²	Ø m	l / min
1	87	10,5	4,9
2	113	12,0	7,1
3	104	11,5	8,4
4	87	10,5	9,5

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet	
8685		4	17,5 x 24 x 8,5	20 x 30 x 33	0,019	1,27	192	8 000625 086856

IDROJET 2000

8694



Rotating 3-arm sprinkler constructed entirely in ABS. Special rounded design enables easy movement over lawn. Adjustable nozzles optimise performance also at low pressure. Covers circular areas with light rain effect. Irrigated area max 113 m².

Bar	m ²	Ø m	l / min
1	75	9,8	7,0
2	113	12,0	9,9
3	104	11,5	11,9
4	95	10,0	13,3

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet	
8694		4	17,5 x 24 x 8,5	20 x 30 x 33	0,019	1,31	192	8 000625 086948

SPIKE-JET

8661



Static sprinkler that can be positioned where needed using the special shaped stake, designed to guarantee maximum stability in the ground. It evenly waters circular areas. Quick-Click standard connection. Irrigated area max 54 m².

Bar	m ²	Ø m	l / min
1	28	6,0	17,5
2	44	7,5	24,7
3	53	8,0	30,3
4	54	8,5	34,0

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet	
8661		5	15,4 x 30 x 7,2	40 x 18 x 18	0,013	0,57	350	

SPRAY-JET

8663



Rotating 2-arm sprinkler with adjustable nozzles. It can be positioned where needed using the special shaped stake, designed to guarantee maximum stability in the ground. Covers circular areas with light rain effect. Quick-Click standard connection. Irrigated area max 64 m².

Bar	m ²	Ø m	l / min
1	64	9,0	4,2
2	64	9,0	5,9
3	55	8,5	7,0
4	55	8,5	7,7

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet	
8663		5	15,4 x 30 x 7,2	40 x 18 x 18	0,013	0,73	350	

VARIO-JET

8662



Multifunction static sprinkler. It features four different jets, which can be selected by turning the head: spray, blade jet, 360°, 180°. The stake has been designed to guarantee maximum stability. Quick-Click standard connection. Irrigated area max 64 m².

Bar	m ²	Ø m	l / min
1	20	5,0	5,6
2	38	7,0	8,1
3	64	9,0	9,8
4	50	8,0	11,5

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet	
8662		5	15,4 x 30 x 7,2	40 x 18 x 18	0,013	0,83	350	





PULSATING SPRINKLERS

Pulsating sprinklers are the ideal solution for watering at long distances: with the Impact line, Claber takes performance and versatility to new heights.

The head design guarantees that the jet is well distributed, with no water leakage from the sides.

The reverse mechanism means you can water a targeted area between 0° and 360°.

Alternatively, you can lift up the mechanism so that the head turns freely and waters the full circular area evenly.

The stainless-steel pin and wear-resistant bronze bushing guarantee maximum durability.

The steel tripod with an epoxy powder coating is ultra-stable and height-adjustable (tripod kit, complete with threaded tube).



3/4" (20-27 mm) IMPACT FEMALE HEAD

8705



Pulsating sprinkler head providing 0° to 360° circle coverage or continuous rotation.
3/4" (20-27 mm) female thread.
Diffuser screw assures even water distribution.
Self-adjusting up to 4 bar, adjustment device for optimal setting at high water pressures.
Stainless steel pin and wear-resistant bronze bushing.

Bar	m ²	Ø m	l / min
1	214	16,5	9,3
2	330	20,5	11,9
3	380	22,0	14,8
4	397	22,5	16,9

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet
8705		5	15,4 x 24 x 4,8	28 x 13 x 25	0,009	0,89	360



IMPACT ON STAKE

8707

Pulsating sprinkler head providing 0° to 360° circle coverage or continuous rotation, mounted on steady twin-point stake. Diffuser screw assures even water distribution. Self-adjusting up to 4 bar, adjustment device for optimal setting at high water pressures. Stainless steel pin and wear-resistant bronze bushing. Irrigated area max 397 m².

Bar	m ²	Ø m	l / min
1	214	16,5	9,3
2	330	20,5	11,9
3	380	22,0	14,8
4	397	22,5	16,9

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet	
8707		5	10,7 x 28 x 4,5	28 x 13 x 25	0,009	1,78	360	8 000625 087075

IMPACT PLASTIC SPIKE

8708

Pulsating sprinkler head providing 0° to 360° circular coverage or continuous rotation, mounted on twinpoint plastic stake. Diffuser screw assures even water distribution. Self-adjusting up to 4 bar, adjustment device for optimal setting at high water pressures. Stainless steel pin and wear-resistant bronze bushing. Irrigated area max 397 m².

Bar	m ²	Ø m	l / min
1	214	16,5	9,3
2	330	20,5	11,9
3	380	22,0	14,8
4	397	22,5	16,9

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet	
8708		5	16 x 7 x 39	20 x 39,5 x 19,5	0,016	1,26	240	8 000625 087082

IMPACT TRIPOD

8709

Pulsating sprinkler head providing 0° to 360° circle coverage or continuous rotation, mounted on steady aluminium tripod. "L" water connection at base. Diffuser screw assures even water distribution. Self-adjusting up to 4 bar, adjustment device for optimal setting at high water pressures. Stainless steel pin and wear-resistant bronze bushing. Irrigated area max 491 m².

Bar	m ²	Ø m	l / min
1	227	17,0	9,3
2	346	21,0	11,9
3	437	23,6	14,8
4	491	25,0	16,9

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet	
8709		4	9,7 x 38 x 6	18 x 40 x 18	0,012	1,81	280	8 000625 087099

IMPACT TRIPOD KIT

8715

Pulsating sprinkler head providing 0° to 360° circle coverage or continuous rotation, mounted on tripod with adjustable opening and height. "L" water connection at base. Diffuser screw assures even water distribution. Self-adjusting up to 4 bar, adjustment device for optimal setting at high water pressures. Stainless steel pin and wear-resistant bronze bushing. Steel tripod with epoxy powder paint finish, with 3/4" (20-27 mm) threaded aluminium tube for height adjustment. Tool-free assembly, comes in practical compact package. Irrigated area max 572 m².

Bar	m ²	Ø m	l / min
1	296	19,4	9,3
2	401	22,6	11,9
3	531	26,0	14,8
4	572	27,0	16,9

code	packaging	qty	pack size (cm)	box size (cm)	volume (m ³)	weight (kg)	pcs/pallet	
8715		2	12 x 59,5 x 8,8	60 x 26 x 10	0,016	4,27	96	8 000625 087150

									
		8740	8748	8753	8743	8654	8656	8658	8660
TYPE		OSCILLATING				STATIC			
SUPPORT		sled	sled	sled	sled	sled	sled	sled	stake
MATERIALS		Aluminium > ABS <	Aluminium > ABS <	Aluminium > ABS <	Aluminium > ABS <	> ABS <	> PP <	> PP <	> PP <
QUICK-CLICK CONNECTION		✓	✓	✓	✓	✓	✓	✓	✓
FUNCTIONS		4	5	5	5	6	1	1	1
WATERING PATTERNS									
									
									
									
									
									
OPERATING PRESSURE (BAR)		1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4
IRRIGATED AREA (m²)	min	78 m ²	98 m ²	100 m ²	83 m ²	36 m ²	19 m ²	47 m ²	30 m ²
	max	181 m ²	192 m ²	320 m ²	290 m ²	64 m ²	28 m ²	63 m ²	40 m ²
AREA (m)	min	11,0 x 7,0	11,5 x 8,5	10,5 x 9,5	10,1 x 8,2	6,00			
	max	16,0 x 11,0	17,5 x 11	19,2 x 16,7	19,9 x 14,6	8,00			
DIAMETER (m)	min						4,00	8,00	6,00
	max						5,00	9,00	7,00
FLOW RATE (l/min)	min	8,00	9,10	10,50	11,80	17,50	18,00	18,00	7,80
	max	15,00	15,70	21,00	25,00	34,00	35,00	30,00	14,80

											
8661	8662	8675	8685	8694	8663	8705	8707	8708	8709	8715	9623
STATIC		ROTATING				PULSATING					
stake	stake	base	base	base	stake		stake	stake	tripod	tripod	stake
> PP <	> PP <	> ABS <	> ABS <	> ABS <	> PP < > ABS <	> ABS <	Steel > ABS <	> PP < > ABS <	Aluminium > ABS <	Steel Aluminium > ABS <	Chrome-plated metal
✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓
1	4	1	1	1	1	2	2	2	2	2	2
											
											
											
											
1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 3
28 m ²	20 m ²	123 m ²	87 m ²	75 m ²	55 m ²	214 m ²	214 m ²	214 m ²	227 m ²	296 m ²	255 m ²
54 m ²	64 m ²	177 m ²	113 m ²	113 m ²	64 m ²	397 m ²	397 m ²	397 m ²	491 m ²	572 m ²	500 m ²
6,00	5,00	12,50	10,50	9,80	8,50	16,50	16,50	16,50	17,00	19,40	18
8,50	9,00	15,00	12,00	12,00	9,00	22,50	22,50	22,50	25,00	27,00	25
8,30	5,60	14,00	4,9	7,00	4,20	9,30	9,30	9,30	9,30	9,30	8,00
16,00	11,50	23,00	9,50	13,30	7,70	16,90	16,90	16,90	16,90	16,90	16,00